

=====

SECTION II - HAZARDOUS INFORMATION

=====

Ingredient Name	CAS Number	Percent	TSCA
ACETONE	67-64-1	15-40	Y
LIGHT ALIPHATIC NAPHTHA	64742-89-8	10-30	Y
TOLUENE	108-88-3	7-13	Y
HEXANE	110-54-3	5-10	Y
CYCLOHEXANE	110-82-7	1-5	Y

=====

SECTION III - PHYSICAL DATA

=====

Appearance/Color: CLEAR OR GREEN

Boiling Range:	0.°F - 315.°F
Evaporation Rate:	Faster than n-Butyl Acetate
% Volatile Weight:	83.09%
% Volatile Volume:	Not Available
Specific Gravity:	0.795
Weight/Volume Measure:	6.6435
Max. VOC:	609.6 g/L

=====

SECTION IV - FIRE AND EXPLOSION HAZARD DANGER

=====

Flammability Class:	IB
Flash Range:	< 0
Explosive Range:	0.%
	0.%

EXTINGUISHING MEDIA:

Foam, dry chemical, carbon dioxide, water spray or fog.

SPECIAL FIREFIGHTING PROCEDURES:

Avoid breathing smoke. Use air supplied rescue equipment for enclosed area. Water tends to spread burning liquid if large amounts used.

UNUSUAL FIRE & EXPLOSION HAZARDS:

Vapors are heavier than air and may travel to an ignition source distant from the material handling point.

=====

SECTION V - HEALTH HAZARD DATA

=====

PERMISSIBLE EXPOSURE LEVEL:

SEE SECTION VIII.

EFFECTS OF OVEREXPOSURE:

INGESTION: Can cause gastrointestinal irritation, nausea and vomiting. Aspiration of material into lungs may cause chemical pneumonitis which can be fatal.

INHALATION: May cause nose or throat irritation. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.

EYES: May cause severe eye irritation and corneal damage.

SKIN: May cause dermatitis. May cause defatting and irritation of the skin.

FIRST AID:

EYES: Flush with large amounts of water, lifting upper and lower

MATERIAL SAFETY DATA SHEET

MSDS Name: TACC CONTACT ADHESIVE FOR LANDAU TOPS AND HEADLINE

MSDS Number: T206

MSDS Last Updated: MAY-21-2001

Printed On: 05/21/01

Page Number: 3 of 5

lids occasionally. Get medical attention.

SKIN: Thoroughly wash exposed area with soap and water. Remove contaminated clothing and launder before re-use.

INGESTION: Do not induce vomiting, keep person warm, quiet, and get medical attention (aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

INHALATION: Remove individual to fresh air and if breathing is difficult, administer oxygen.

SECTION VI - REACTIVITY DATA

Stability: This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

Strong oxidizing agents, strong acids and bases.

CONDITIONS TO AVOID:

Fire, sparks, static electricity.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide, carbon dioxide.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Keep spectators away. Eliminate all ignition sources (flames, hot surfaces and sources of electrical, static or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams and groundwater with spilled material or used absorbent.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, state and federal

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

ACGIH TLV

ACGIH TLV-C

ACGIH STEL

OSHA STEL

OSHA PEL

MATERIAL SAFETY DATA SHEET

MSDS Name: TACC CONTACT ADHESIVE FOR LANDAU TOPS AND HEADLINE

MSDS Number: T206

MSDS Last Updated: MAY-21-2001

Printed On: 05/21/01

Page Number: 4 of 5

ACETONE	500.00 PPM	N/est	750.00 PPM	N/est	1000.00 PPM
LIGHT ALIPHATIC NAPHTHA	100.00 PPM	N/est	N/est	N/est	500.00 PPM
TOLUENE	50.00 PPM	N/est	N/est	N/est	200.00 PPM
HEXANE	400.00 PPM	N/est	500.00 PPM	N/est	500.00 PPM
CYCLOHEXANE	200.00 PPM	N/est	N/est	N/est	200.00 PPM

RESPIRATORY PROTECTION:

If workplace exposure limit of product is exceeded, a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL.

PROTECTIVE GLOVES:

Chemical resistant gloves.

EYE PROTECTION:

Chemical splash goggles in compliance with OSHA regulations are advised.

OTHER PROTECTIVE EQUIPMENT:

To prevent repeated, prolonged skin contact, wear impervious clothing and boots.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container closed when not in use. Store at 60-95 degrees F and out of the sun. Use adequate ventilation to avoid breathing vapors when cover is removed. Ground all equipment when handling flammable solventborne materials.

OTHER PRECAUTIONS:

Containers may be hazardous when empty. Never use welding or cutting torch on or near drum (even when empty).

MATERIAL SAFETY DATA SHEET

MSDS Name: TACC CONTACT ADHESIVE FOR LANDAU TOPS AND HEADLINE

MSDS Number: T206

MSDS Last Updated: MAY-21-2001

Printed On: 05/21/01

Page Number: 5 of 5

SECTION X - ADDITIONAL REGULATORY INFORMATION

-SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
TOLUENE	108-88-3	7-13
HEXANE	110-54-3	5-10
CYCLOHEXANE	110-82-7	1-5

-PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
TOLUENE	108-88-3	7-13

The following ingredients are registered for TSCA 12B

Ingredient Name	CAS Number	Percent
ACETONE	67-64-1	15-40
HEXANE	110-54-3	5-10
CYCLOHEXANE	110-82-7	1-5

DISCLAIMER

***** NOTICE *****

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of TACC. The data on this sheet relates only to the specific material designated herein. TACC assumes no legal responsibility for use or reliance upon these data.
